

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055,0028

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

- a
1. (Original) A method for accessing data in a distributed database environment, comprising:
 - receiving, with a client program, multiple requests for data from a database object satisfying specified search predicates from an application program, wherein each request includes a request for at least one row from the database object;
 - transferring, with the client program, a database command and a rowset parameter indicating a maximum number of rows to return to a server program over a network if the requested row is not maintained by the client program;
 - generating a data block with the server program including rows from the database object satisfying the search predicates in response to the database command, wherein the rows included in the data block do not exceed the rowset parameter;
 - transferring, with the server program, the data block to the client program; and
 - returning, with the client program, at least one requested row from the received data block in response to one request for the at least one row of data from the application program.
 2. (Original) The method of claim 1, wherein the multiple requests specify orientation information for a row from the database object satisfying the specified search predicates.
 3. (Original) The method of claim 1, wherein the server program maintains a maximum block size parameter, and wherein the data block is further generated to not exceed the block size parameter.

A

Arndt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a1
4. (Original) The method of claim 1, wherein the multiple requests received by the client program from the application program comprise single-row fetch requests and the rows from the database object that satisfy the search predicates are returned as part of a scrollable cursor created by the application program.

5. (Original) The method of claim 4, further comprising:
maintaining, with the client program, a first pointer addressing a last accessed row from the received data block and a client cursor addressing a last requested row from the scrollable cursor; and
incrementing the client cursor to an entry in the database object corresponding to the last row returned to the application program.

6. (Original) The method of claim 5, wherein the server program maintains a server cursor addressing the last row from the database object included in a last data block returned to the client program.

7. (Original) The method of claim 6, wherein the client program manages the client cursor to ensure that the correct row is returned from the server in order to satisfy the client requests and wherein the client program is capable of sending a command to the server program to correct the server cursor position.

8. (Original) The method of claim 1, wherein the client program and server program communicate using the Distributed Relational Database Architecture (DRDA).

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a1
9. (Original) The method of claim 1, wherein the search predicates are defined with a database cursor that provides a result table subset of the database object that satisfies the search predicates.

10. (Original) The method of claim 8, wherein the database command transferred by the client program comprises an open cursor command.

11. (Original) The method of claim 8, wherein the database command transferred by the client program comprises a continued request for rows from an open cursor.

12. (Original) The method of claim 1, further comprising:
determining, with the client program, whether the data block includes less rows than the rowset parameter;

determining, with the client program, a difference between the rowset parameter and a number of rows included in the data block if the data block includes less rows than the rowset parameter; and

sending, with the client program, a command to the server program to transmit the difference of rows.

13. (Currently Amended) A method for accessing data in a distributed database environment, comprising:

receiving, with a client program, multiple requests for at least one row of data from a database object satisfying specified search predicates from an application program, wherein each request includes a request for at least one row from the database object satisfying the specified search predicates;

A

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

transferring, with the client program, a database command and a rowset parameter indicating a maximum number of rows to return to a first server program over a network if the requested row is not maintained by the client program;

transferring, with the first server program, a database command and the rowset parameter to a second server program over the network if the requested row is not maintained by the first server program;

generating a first data block with the second server program including rows from the database object satisfying the search predicates in response to the database command, wherein the rows included in the first data block do not exceed the rowset parameter;

transferring, with the first second server program, the first data block to the first server program;

generating a second data block with the first server program including rows from the first data block, wherein the rows in the second data block do not exceed the rowset parameter;

transferring, with the first server program, the second data block to the client program;
and

returning, with the client program, at least one requested row from the received data block in response to one request for the at least one row of data from the application program.

14. (Original) The method of claim 13, wherein the first server program maintains a block limit, wherein a number of rows the first server program includes in the second data block does not exceed the block limit.

15. (Original) The method of claim 14, wherein generating the second data block with the first server program from the rows in the first data block comprises:

adding rows from the first data block to the second data block until a size of the second data block reaches one of the rowset parameter or the block limit; and

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

buffering the rows in the first data block that are not added to the second data block.

A¹
16. (Original) The method of claim 13, wherein the second server program maintains a block limit, wherein a number of rows the second server program includes in the first data block further does not exceed the block limit.

17. (Original) The method of claim 13, wherein the first server program maintains a first block limit and wherein the second data block further does not exceed the first block limit and wherein the second server program maintains a second block limit, wherein the first data block further does not exceed the second block limit.

18. (Original) The method of claim 17, wherein the first block limit is greater than the second block limit and both are less than the limit imposed by the rowset parameter and wherein generating the second data block with the first server program from the rows in the first data block comprises:

adding all the rows from the first data block to the second data block, wherein the rows added to the second data block is less than the rowset parameter;

transmitting, with the first server program, a database command to the second server program requesting a shortfall of rows equal to the rowset parameter minus the number of rows added to the second data block; and

receiving, with the first server program, a third data block from the second server program including the shortfall of rows;

adding, with the first server program, rows from the third data block, up to the first block limit, to the pending second data block;

A

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a1
repeating the sending of a database command to the second server program and the receiving of additional rows until the first block limit is satisfied; and
returning the second data block to the client program.

19. (Original) The method of claim 18, wherein the first and second block limits are less than the rowset parameter size, further comprising:

determining, at the client program, that the number of rows in the second data block is less than the rowset parameter size; and

transmitting, with the client program, a command requesting further rows to include in additional data blocks to send to the client program until the rowset parameter number of rows have been transferred to the client program.

20. (Original) The method of claim 19, further comprising:

transmitting, with the client program, a command to the first server program to clear pending data blocks for the rowset and pending rowset status.

21. (Original) The method of claim 19, wherein the first block limit is less than the second block limit and both are less than the limit imposed by the rowset parameter, and wherein generating the second data block with the first server program further comprises:

adding some of the rows from the first data block to the second data block, up to the first block limit; and

returning the second data block to the client program, and retaining any unsent rows from the first data block.

22. (Original) The method of claim 13, wherein there are additional server programs between the first server program and second server program through which the rows from the database object are transferred,

A

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

23. (Original) A system for accessing data in a distributed database environment, comprising:

- a computer database including at least one database object;
a client computer;
a server computer;
a network enabling communication between the client computer and server computer;
a client program executed by the client computer to perform:

(i) receiving multiple requests for data from a database object satisfying specified search predicates from an application program, wherein each request includes a request for at least one row from the database object;

(ii) transferring a database command and a rowset parameter indicating a maximum number of rows to return to the server program over a network if the requested row is not maintained by the client program;

a server program executed by the client computer to perform:

(i) generating a data block including rows from the database object satisfying the search predicates in response to the database command from the client program, wherein the rows included in the data block do not exceed the rowset parameter;

(ii) transferring the data block to the client program, wherein the client program returns at least one requested row from the received data block in response to one request for the at least one row of data from the application program.

24. (Original) The system of claim 23, wherein the multiple requests specify orientation information for a row from the database object satisfying the specified search predicates.

25. (Original) The system of claim 23, wherein the server program maintains a maximum block size parameter, and wherein the data block is further generated to not exceed the block size parameter.

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a1
26. (Original) The system of claim 23, wherein the multiple requests received by the client program from the application program comprise single-row fetch requests and the rows from the database object that satisfy the search predicates are returned as part of a scrollable cursor created by the application program.

27. (Original) The system of claim 26, wherein the client program further performs:
maintaining a first pointer addressing a last accessed row from the received data block and a client cursor addressing a last requested row from the scrollable cursor; and
incrementing the client cursor to an entry in the database object corresponding to the last row returned to the application program.

28. (Original) The system of claim 27, wherein the server program maintains a server cursor addressing the last row from the database object included in a last data block returned to the client program.

29. (Original) The system of claim 28, wherein the client program manages the client cursor to ensure that the correct row is returned from the server in order to satisfy the client requests and wherein the client program is capable of sending a command to the server program to correct the server cursor position.

30. (Original) The system of claim 23, wherein the client program and server program communicate using the Distributed Relational Database Architecture (DRDA).

31. (Original) The system of claim 23, wherein the search predicates are defined with a database cursor that provides a result table subset of the database object that satisfies the search predicates.

A

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

32. (Original) The system of claim 31, wherein the database command transferred by the client program comprises an open cursor command.

33. (Original) The system of claim 31, wherein the database command transferred by the client program comprises a continued request for rows from an open cursor.

34. (Original) The system of claim 23, wherein the client program further performs:
determining whether the data block includes less rows than the rowset parameter;
determining a difference between the rowset parameter and a number of rows included in the data block if the data block includes less rows than the rowset parameter; and
sending a command to the server program to transmit the difference of rows.

35. (Currently Amended) A system for accessing data in a distributed database environment, comprising:
a distributed computing environment including at least one client program, first server program, second server program, and at least one database object;
a network enabling communication among the client program, first server program, and second server program;
means, performed by the client program, for receiving multiple requests for at least one row of data from a database object satisfying specified search predicates from an application program, wherein each request includes a request for at least one row from the database object satisfying the specified search predicates;
means, performed by the client program, for transferring a database command and a rowset parameter indicating a maximum number of rows to return to the first server program over the network if the requested row is not maintained by the client program;

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a¹
means, performed by the first server program, for transferring a database command and the rowset parameter to the second server over the network if the requested row is not maintained by the first server program;

means, performed by the second server program, for generating a first data block including rows from the database object satisfying the search predicates in response to the database command from the first server program, wherein the rows included in the first data block do not exceed the rowset parameter;

means, performed by the ~~first~~ second server program, for transferring the first data block to the first server program;

means, performed by the first server program, for generating a second data block including rows from the first data block, wherein the rows in the second data block do not exceed the rowset parameter;

means, performed by the first server program, for transferring the second data block to the client program; and

means, performed by the client program, for returning at least one requested row from the received data block in response to one request for the at least one row of data from the application program.

36. (Original) The system of claim 35, wherein the first server program maintains a block limit, wherein a number of rows the first server program includes in the second data block does not exceed the block limit.

A

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

37. (Original) The system of claim 36, wherein the means for generating the second data block with the first server program from the rows in the first data block further performs:
adding rows from the first data block to the second data block until a size of the second data block reaches one of the rowset parameter or the block limit; and
buffering the rows in the first data block that are not added to the second data block.

38. (Original) The system of claim 35, wherein the second server program maintains a block limit, wherein a number of rows the second server program includes in the first data block further does not exceed the block limit.

39. (Original) The system of claim 35, wherein the first server program maintains a first block limit and wherein the second data block further does not exceed the first block limit and wherein the second server program maintains a second block limit, wherein the first data block further does not exceed the second block limit.

40. (Original) The system of claim 39, wherein the first block limit is greater than the second block limit and both are less than the limit imposed by the rowset parameter, and wherein the means for generating the second data block with the first server program from the rows in the first data block performs:

adding all the rows from the first data block to the second data block, wherein the rows added to the second data block is less than the rowset parameter;

transmitting, with the first server program, a database command to the second server program requesting a shortfall of rows equal to the rowset parameter minus the number of rows added to the second data block;

receiving, with the first server program, a third data block from the second server program including the shortfall of rows;

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a1
adding rows from the third data block, up to the first block limit, to the pending second data block;

repeating the sending of a database command to the second server program and the receiving of additional rows until the first block limit is satisfied; and
returning the second data block to the client program.

41. (Original) The system of claim 40, wherein the first and second block limits are less than the rowset parameter size, further comprising:

means, performed by the client program, for determining whether the number of rows in the second data block is less than the rowset parameter size; and

means, performed by the first client program, for transmitting a command requesting further rows to include in additional data blocks to send to the client program until the rowset parameter number of rows have been transferred to the client program.

42. (Original) The system of claim 41, further comprising:

means, performed by the client program, for transmitting a command to the first server program to clear pending data blocks for the rowset and pending rowset status.

43. (Original) The system of claim 41, wherein the first block limit is less than the second block limit and both are less than the limit imposed by the rowset parameter, and wherein the means for generating the second data block with the first server program further performs:

adding some of the rows from the first data block to the second data block, up to the first block limit; and

returning the second data block to the client program, and retaining any unsent rows from the first data block.

A

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a1
44. (Original) The system of claim 35, further comprising additional server programs between the first server program and second server program through which the rows from the database object are transferred.

45. (Original) Multiple computer readable media including instructions in a client program and server program that communicate over a network to cause computers to enable access to data in a distributed database environment by:

receiving, with the client program, multiple requests for data from a database object satisfying specified search predicates from an application program, wherein each request includes a request for at least one row from the database object;

transferring, with the client program, a database command and a rowset parameter indicating a maximum number of rows to return to the server program over a network if the requested row is not maintained by the client program;

generating a data block with the server program including rows from the database object satisfying the search predicates in response to the database command, wherein the rows included in the data block do not exceed the rowset parameter;

transferring, with the server program, the data block to the client program; and
returning, with the client program, at least one requested row from the received data block in response to one request for the at least one row of data from the application program.

46. (Original) The multiple computer readable media of claim 45, wherein the multiple requests specify orientation information for a row from the database object satisfying the specified search predicates.

47. (Original) The multiple computer readable media of claim 45, wherein the server program maintains a maximum block size parameter, and wherein the data block is further generated to not exceed the block size parameter,

A

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

48. (Original) The multiple computer readable media of claim 45, wherein the multiple requests received by the client program from the application program comprise single-row fetch requests and the rows from the database object that satisfy the search predicates are returned as part of a scrollable cursor created by the application program.

49. (Original) The multiple computer readable media of claim 48, further comprising: maintaining, with the client program, a first pointer addressing a last accessed row from the received data block and a client cursor addressing a last requested row from the scrollable cursor; and

incrementing the client cursor to an entry in the database object corresponding to the last row returned to the application program.

50. (Currently Amended) The multiple computer readable media of claim 49, wherein the server program maintains a server cursor addressing the last row from the database object included in a last data block returned to the client program.

51. (Original) The multiple computer readable media of claim 50, wherein the client program manages the client cursor to ensure that the correct row is returned from the server in order to satisfy the client requests and wherein the client program is capable of sending a command to the server program to correct the server cursor position.

52. (Original) The multiple computer readable media of claim 45, wherein the client program and server program communicate using the Distributed Relational Database Architecture (DRDA),

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a) 53. (Original) The multiple computer readable media of claim 45, wherein the search predicates are defined with a database cursor that provides a result table subset of the database object that satisfies the search predicates.

54. (Original) The multiple computer readable media of claim 52, wherein the database command transferred by the client program comprises an open cursor command.

55. (Original) The multiple computer readable media of claim 45, further comprising determining, with the client program, whether the data block includes less rows than the rowset parameter;

determining, with the client program, a difference between the rowset parameter and a number of rows included in the data block if the data block includes less rows than the rowset parameter; and

sending, with the client program, a command to the server program to transmit the difference of rows,

56. (Currently Amended) Multiple computer readable media including instructions in a client program, first server program, and second server program that communicate over a network to cause computers to enable access to data in a network distributed database environment by:

receiving, with the client program, multiple requests for at least one row of data from a database object satisfying specified search predicates from an application program, wherein each request includes a request for at least one row from the database object satisfying the specified search predicates;

transferring, with the client program, a database command and a rowset parameter indicating a maximum number of rows to return to the first server program over a network if the requested row is not maintained by the client program;

A

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a1
transferring, with the first server program, a database command and the rowset parameter to a second server program over the network if the requested row is not maintained by the first server program;

generating a first data block with the second server program including rows from the database object satisfying the search predicates in response to the database command, wherein the rows included in the first data block do not exceed the rowset parameter;

transferring, with the first second server program, the first data block to the first server program;

generating a second data block with the first server program including rows from the first data block, wherein the rows in the second data block do not exceed the rowset parameter;

transferring, with the first server program, the second data block to the client program;
and

returning, with the client program, at least one requested row from the received data block in response to one request for the at least one row of data from the application program.

57. (Original) The multiple computer readable media of claim 56, wherein the first server program maintains a block limit, wherein a number of rows the first server program includes in the second data block does not exceed the block limit.

58. (Original) The multiple computer readable media of claim 57, wherein generating the second data block with the first server program from the rows in the first data block comprises:

adding rows from the first data block to the second data block until a size of the second data block reaches one of the rowset parameter or the block limit; and

buffering the rows in the first data block that are not added to the second data block.

A

Amdt. dated January 12, 2004
Reply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a1
59. (Original) The multiple computer readable media of claim 56, wherein the second server program maintains a block limit, wherein a number of rows the second server program includes in the first data block further does not exceed the block limit.

60. (Original) The multiple computer readable media of claim 56, wherein the first server program maintains a first block limit and wherein the second data block further does not exceed the first block limit and wherein the second server program maintains a second block limit, wherein the first data block further does not exceed the second block limit.

61. (Original) The multiple computer readable media of claim 60, wherein the first block limit is greater than the second block limit and both are less than the limit imposed by the rowset parameter, and wherein generating the second data block with the first server program from the rows in the first data block comprises:

- adding all the rows from the first data block to the second data block, wherein the rows added to the second data block is less than the rowset parameter;

- transmitting, with the first server program, a database command to the second server program requesting a shortfall of rows equal to the rowset parameter minus the number of rows added to the second data block;

- receiving, with the first server program, a third data block from the second server program including the shortfall of rows;

- adding, with the first server program, rows from the third data block, up to the first block limit, to the pending second data block;

- repeating the sending of a database command to the second server program and the receiving of additional rows until the first block limit is satisfied; and

- returning the second data block to the client program.

A

Amdt. dated January 12, 2004
Rcply to Office action of 10/10/2003

Serial No. 09/819,476
Docket No. STL920000078US1
Firm No. 0055.0028

a' 62. (Original) The multiple computer readable media of claim 55, wherein the first and second block limits are less than the rowset parameter size, further comprising:

determining, at the client program, that the number of rows in the second data block is less than the rowset parameter size; and

transmitting, with the client program, a command requesting further rows to include in additional data blocks to send to the client program until the rowset parameter number of rows have been transferred to the client program.

63. (Original) The multiple computer readable media of claim 62, further comprising: transmitting, with the client program, a command to the first server program to clear pending data blocks for the rowset and pending rowset status.

64. (Original) The multiple computer readable media of claim 62, wherein the first block limit is less than the second block limit and both are less than the limit imposed by the rowset parameter, and wherein generating the second data block with the first server program further comprises:

adding some of the rows from the first data block to the second data block, up to the first block limit; and

returning the second data block to the client program, and retaining any unsent rows from the first data block.

A